

# SP BANDER



## Key Features:

- Available in either paper or poly rolls
- Adjustable backstops for feeding ease
- LCD readout for operation adjustments
- Adjustable lag time for variable feeding
- Adjustable tension for delicate jobs
- Optional Jumbo roll stand available for high volume users
- Closed arch system for feeding ease and durability
- Quick release to cut and eject the banding in case of misfeeds
- Manual, Foot-pedal, or automatic sensor-driven operation



Banding Specification	30mm (1.2") wide x 100-120 microns (thickness)*
Banding Types	Poly film or Paper banding
Banding Roll Size	150 metre (492') length *
Control System	Manual, Foot Pedal, Automatic
Electrical	110V, 50Hz/60Hz, 10A
Maximum Input Size	460mm (18") x 200mm (7.9")
Minimum Input Size	30mm (1.2") x 10mm (0.4")
Banding Speed	20 pieces/ minute **
Sealing Method	Thermal Sealing (self-welding tape)
Feeder	Handfed

\* based on Graphic Whizard supplied banding rolls  
 \*\* dependent on operator speed

GRAPHIC WHIZARD AUTHORIZED DEALER:



**MyBinding**  
 When Image Matters.

**mybinding.com**  
**1-800-944-4573**

**WWW.GRAPHICWHIZARD.COM**